



**DECLARATION OF PERFORMANCE**  
**N. 002BICO DOP del 27/06/2013**

1. Unique identification code of the Product-type:	Dry- pressed ceramic tiles with low water absorption $E_b > 10\%$ ,																				
2. Intended use:	Ceramic tile, dry pressed, for internal floors and walls																				
3. Name and contact address of the manufacturer:	ASCOT CERAMICHE via Croce, 80 41014 Solignano ( MO )																				
4. System of assessment and verification of constancy of performance of the construction products ( AVCP):	System 4																				
5. Name and identification number of notified body, if applicable :	Not applicable																				
6. Declared performance:	<table border="1"> <thead> <tr> <th>Essential characteristics</th> <th>Performance</th> <th>Technical specifications</th> </tr> </thead> <tbody> <tr> <td>Reaction to fire</td> <td>A1</td> <td rowspan="7">EN 14411:2012</td> </tr> <tr> <td>Release of dangerous substances</td> <td></td> </tr> <tr> <td>- Lead</td> <td>NPD</td> </tr> <tr> <td>- Cadmium</td> <td>NPD</td> </tr> <tr> <td>Adhesion resistance Cementitious adhesive C2 (except cold)</td> <td><math>&gt; 1 \text{ N/mm}^2</math></td> </tr> <tr> <td>Thermal shock resistance</td> <td>NPD</td> </tr> <tr> <td>Durability: - internal use - External use:Frost resistance</td> <td>Passed NPD</td> </tr> </tbody> </table>			Essential characteristics	Performance	Technical specifications	Reaction to fire	A1	EN 14411:2012	Release of dangerous substances		- Lead	NPD	- Cadmium	NPD	Adhesion resistance Cementitious adhesive C2 (except cold)	$> 1 \text{ N/mm}^2$	Thermal shock resistance	NPD	Durability: - internal use - External use:Frost resistance	Passed NPD
Essential characteristics	Performance	Technical specifications																			
Reaction to fire	A1	EN 14411:2012																			
Release of dangerous substances																					
- Lead	NPD																				
- Cadmium	NPD																				
Adhesion resistance Cementitious adhesive C2 (except cold)	$> 1 \text{ N/mm}^2$																				
Thermal shock resistance	NPD																				
Durability: - internal use - External use:Frost resistance	Passed NPD																				
7. Declaration:	The performance of the product identified in point 1 and 2 is in conformity with the declared performance in point 6. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.																				

Signed for and on behalf of the manufacturer by :                      Simone Manicardi      Technical manager

Solignano 27/06/2013

Signature